



FULL MODULE UNIT - 2 CAST-IRON CHARGRILLS OVER 1 TANK

BRIDGE UNIT

Pro 900

Summary

Energy :

GAS

Code :

V02272

Designation :

R-G2GRILPIER-V-1B

Dimensions (W x D x H) :

850 x 900 x 320/380 mm

Power : 30 kW (gas)

Voltage/Electric p. :

Weight :

DEVICE DESCRIPTION


General description

Chassis :

Support frame in AISI 304 stainless steel, thickness 15 to 30/10, assembled by high intensity.

Top :

Top (frame) in AISI 304 stainless steel, 30/10 thick, with 55 mm front flanged edge and plywood.



Above :

- . Refractory briquette grill
- . AISI304 stainless steel hearth with plume
- . 2 stainless steel V cooking grids 365 x 650 mm with handles and height adjustment device on 3 levels
- . Stainless steel stone support grid
- . AISI304 stainless steel juice collector in the upper part
- . Multi - ramp burner in anti - corrosion treated steel, P 2 x 13 kW with safety thermocouple
- . "Stop / full-fire / slow-down" valve with backlash adjustment
- . Refractory briquettes for 1st charge
- . AISI304 stainless steel cleanliness drawer on the front

Below:

- . None -> to place or to hang

Natural gas flow G20/20 :

2,75

Propane gas flow G31/37 :

2,02

OPTIONS

CODE

Electric spark ignition 1-230V+E/0,002 Kw

V01013

S/S rear panel fitted in factory W : 840 x H : 645 mm

V01290

ACCESSORIES

CODE






Removable splash guard for 1 griddle

V01562

Recharge "refractory briquettes" set of 97 briquettes for 2 grills

V02253



 Connexion gaz Gas connection Gasanschluss Conexión gas	 Connexion électrique Electric connection Elektrische verbindung Conexión eléctrica	 Options Optionen Ausstattung Opciones	 Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría	 Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente	 Connexion eau adoucie Softened water connection Weichwasseranschluss Conexión agua suavizada ≤ 3bars-7°F Wasserzulauf (gefiltertes wasser ≤ 3bars-7°F/3H) Conexión agua filtrada ≤ 3 bars-4 lb.-7°F	 Ecoulement eaux usées sewage outflow wasserlauf desagüe
 						
    Ø 15x21 (1/2")  1~230V + PE Ø1.50mm²    V02272 PRO000R-C2GRILPIER-V						



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr

