



FULL MODULE UNIT - 2 CAST-IRON CHARGRILLS OVER 1 TANK

BRIDGE UNIT

Pro 900

Summary

Energy :

GAS

Code :

V02385

Designation :

R-G2GRILPIER -1B

Dimensions (W x D x H) :

850 x 900 x 320/380 mm

Power : 30 kW (gas)

Voltage/Electric p. :

Weight :

DEVICE DESCRIPTION


General description

Chassis :

Support frame in AISI 304 stainless steel, thickness 15 to 30/10, assembled by high intensity.

Top :

Top (frame) in AISI 304 stainless steel, 30/10 thick, with 55 mm front flanged edge and plywood.



. 1 stainless steel fireplace with plume

Above :

. 2 refractory bricks grills:

. 400 x 470 cooking grid in openwork cast iron, with handles and height adjustment device on 3 levels

. Stainless steel support grid for refractory bricks (12 mm diameter rounds)

. Multi-rail burner in stainless steel tube, power 13 kW with pilot burner and thermocouple safety device

. "Stop - full fire - slow down" faucet with backlash

. Stainless steel 18-10 frame cleanliness rack (only if several stoves):

. Assembly frame in 18-10 stainless steel tube 30 x 60 x 1 mm and profiles in 18-10 stainless steel sheet 30/10 thick, with plates for fixing the stoves

Natural gas flow G20/20 :

2,75

Propane gas flow G31/37 :

2,02

OPTIONS

CODE

Electric spark ignition 1-230V+E/0,002 Kw

V01013

S/S rear panel fitted in factory W : 840 x H : 645 mm

V01290

ACCESSORIES

CODE






Removable splash guard for 1 griddle

V01562

Recharge "refractory briquettes" set of 97 briquettes for 2 grills

V02253



 Connexion gaz Gas connection Gasanschluss Conexión gas	 Connexion électrique Electric connection Elektrische verbindung Conexión eléctrica	 Options Opciones Ausstattungs Aulantage Opciones	 Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría	 Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente	 Connexion eau adoucie Soft water connection Weichwasseranschluss Softened water connection ≤ 3bars-7°F Wasserzulauf (gefiltertes wasser ≤ 3bars-7°F/3H) Conexión agua aducida ≤ 3 bars-4 lb. 7°F	 Ecoulement eaux usées sewage outflow wasserlauf desague
 						
  						
     Ø 15x21 (1/2") 1~230V + PE Ø1.50mm² V02385 PRO000R-C2GRILPIER-O-1B						



LES AUTHENTIQUES DE LA CUISSON

CHARVET

1170 rue principale - BP3 - 38850 Charavines - FRANCE

Tél: +33 (0)4 76 06 64 22 - info@charvet.fr

www.charvet.fr

