

2 CAST IRON GRIDDLE

BRIDGE UNIT

GENERAL DESCRIPTION

- Top :
AISI 304 stainless steel top 2 mm thick with a 55 mm high edge having 18 mm radius and return to under
- Chassis :
one-piece seam welded stainless steel chassis 2 mm thick duct at the back
- General :
AISI 304 side and front panels 1.2 mm thick
Enamel control panel
Chrome coated aluminium knob

Natural gas
G20/20 :

-

Propane gas
G31/37 :

-

REFERENCE : 80-R-E2CHRL



APPLIANCE DESCRIPTION

Dimensions (mm) : W 400 x D 700 x H 280

- Top :
1 inclined chrome coated (50 µm) smooth griddle plate measuring 350x495 mm
Grease collection drawer.
Heating element rated 3.3 kW each.
Thermostatic control valve (130° to 350°C)
- Bridge unit
- Electrical rating : 6.6 kW 3-400 V+E

CODE	DIMENSIONS	VOLTAGE	POWER	WEIGHT
V07032	800 X 700 X 280 mm	3-400 V+E	ELEC 6.6 kW	-

OPTIONS	CODE
Base unit 800 open	V07057
Base unit with 4xGN2/1 storage	V07058
Hinged doors	V07062
Electric hot cupboard in base 4 x GN2/1 (1-230V+E) - 1.13 kW	V07064
-	-
-	-
-	-
-	-
-	-

ACCESSORIES	CODE
Ribbed chrome griddle plate	V07092
Mixed smooth/ribbed griddle plate	V07093
S/S clip on plinth panels	V07084



Connexion gaz Gas connection Gasanschluss Conexión gas	Connexion électrique Electric connection Elektrische verbindung Conexión eléctrica	Options Options Aufanfrage Opciones	Connexion eau froide Cold water connection Kaltwasseranschluss Conexión agua fría	Connexion eau chaude Hot water connection Warmwasseranschluss Conexión agua caliente	Connexion eau adoucie Softened water connection ≤ 3bars-L.h...7°F Wasserzulauf (gefiltertes wasser ≤ bars-ab. 7°GH) Conexión agua blanda ≤ 3 bars-L.h...7°F	Ecoulement eaux usées sewage outflow wasserablauf desagüe
					3~400 V + PE Ø 1.50mm²	V07032 PRO700-80-E2-GRILL-CHR

Charvet se réserve le droit de modifier les caractéristiques techniques de ses matériels sans préavis.