

1 OPEN BURNER

BRIDGE UNIT

GENERAL DESCRIPTION

- Top :
AISI 304 stainless steel top 2 mm thick with a 55 mm high edge having 18 mm radius and return to under

- Chassis :
one-piece seam welded stainless steel chassis 2 mm thick duct at the back

- General :
AISI 304 side and front panels 1.2 mm thick
Enamel control panel
Chrome coated aluminium knob



APPLIANCE DESCRIPTION

Dimensions (mm) : W 400 x D 700 x H 280

- Top :
1 "Crown" open burner at 10 kW with 330x520 mm nickel coated pan support.
Removable enamel spillage tray.
Flame failure safety cut out thermocouple - pilot ignition - recessed low and high heat control.
Low stainless steel spillage tray.

- Bridge unit

Gas rating : 10 kW

Natural gas G20/20 :	1.38 m3/h
Propane gas G31/37 :	1.01 kg/h

REFERENCE : 40-R-G1FN

CODE	DIMENSIONS	VOLTAGE	POWER	WEIGHT
V07123	400 X 700 X 280 mm	-	GAS 10 kW	-

OPTIONS	CODE
Base unit 400 open	V07053
Base unit with storage GN1/1 (requires drain tap to front)	V07054
Base unit + drawers (Requires drain tap to front)	V07074
Hinged door	V07061
Electric hot cupboard in base 4 x GN1/1 (1-230V+E) - 0.75kW	V07063
Electric ignition (1-230V+E)	V07066
-	-
-	-
-	-

ACCESSORIES	CODE
S/S clip on plinth panels	V07082
-	-
-	-